

DEMO SETS

Code	Description	Includes
5025-A1	26 pieces set	Digital caliper, depth gauge, chamfer gauge, inside groove caliper, outside neck caliper, outside micrometer, internal micrometer, digital indicator, bore gauge, thickness gage, internal chamfer gage, digital level, plug gauge and ring gauge
5025-B1	2 pieces set	Comparison gauge
5025-C1	7 pieces set	Digital measuring tape, torque wrench, roughness tester, thickness gauge, hardness tester and videoscope
5025-D	1 piece set	Microscope



















5025-A1/5025-C1/5025-D set box,
dimension: 635x475x250mm










5025-B1 set box,
dimension: 516x337x118mm

DETAILS

Code	Includes	Description	Specification	Picture
5025-A1	1108-150	Digital caliper	1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005"	
	6144	Accessory set or digital calipers	1. Suitable for 0-150mm/0-6" and 0-200mm/0-8" digital calipers(thickness of lower jaws≤3.7mm)	
	6147-A1	Groove Points for digital calipers	1. Suitable for 0-150mm/0-6" and 0-200mm/0-8" digital calipers(thickness of lower jaws≤3.7mm)	
	1113-150	Built-in wireless digital caliper	1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005"	
	1140-25WL	Built-in wireless mini digital depth gauge with round bar	1. Range: 0-25mm/0-1" 2. Resolution: 0.01mm/0.0005"	
	1141-150AWL	Built-in wireless digital depth gauge	1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005"	
	1148-200WL	Built-in wireless digital depth gauge with round depth bar	1. Range: 0-200mm/0-8" 2. Resolution: 0.01mm/0.0005"	
	1180-6WL	Built-in wireless digital chamfer gauge	1. Range: 0-10mm/0-0.39" 2. Resolution: 0.01mm/0.0005"	
	1176-150WL	Built-in wireless digital inside groove caliper	1. Range: 9-150mm/0.35-6" 2. Resolution: 0.01mm/0.0005"	
	1187-150AWL	Built-in wireless digital outside neck caliper	1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005"	
	1526-200WL	Built-in wireless digital caliper with interchangeable points	1. Range: 0-224mm/0-8.8" 2. Resolution: 0.01mm/0.0005"	
	3112-25WL	Built-in wireless waterproof digital outside micrometer	1. Range: 0-25mm/0-1" 2. Resolution: 0.001mm/0.00005"	

Code	Includes	Description	Specification	Picture
5025-A1	3113-20WL	Built-in wireless digital three points internal micrometer	1. Range: 16-20mm/0.63-0.79" 2. Resolution: 0.001mm/0.00005"	
	3540-25WL	Built-in wireless digital depth micrometer	1. Range: 0-25mm/0-1" 2. Resolution: 0.001mm/0.00005"	
	3507-25	Bluetooth digital indicating micrometer	1. Range: 0-25mm/0-1" 2. Resolution: 0.0001mm/0.000005"	
	3358-25AWL	Built-in wireless digital micrometers/snap gauge	1. Range: 0-25mm/0-1" 2. Resolution: 0.001mm/0.00005"	
	2124-25+ 2508-10FWL	Pistol grip three points bore gauge	1. Range: 20-25mm/0.78-1" 2. Resolution: 0.001mm/0.00005"	
	2508-10FWL	Built-in wireless digital indicator	1. Range: 0-12.7mm/0-0.5" 2. Resolution: 0.001mm/0.00005"	
	2510-101F	Built-in wireless high precision digital indicator	1. Range: 0-12.7mm/0-0.5" 2. Resolution: 0.001mm/0.00005"	
	2122-35A	Digital bore gauge	1. Range: 18-35mm/0.7-1.3" 2. Resolution: 0.002mm/0.0001" or switch to 0.01mm/0.0005"	
	2871-101	Digital thickness gauge	1. Range: 0-10mm/0-0.4" 2. Resolution: 0.001mm/0.00005"	
	2937-101	Digital internal chamfer gauge	1. Range: 1-20mm/0.04-0.78" 2. Resolution: 0.01mm/0.0005"	
	2932-451	Digital internal measuring gauge	1. Range: 24-50mm/0.95-2" 2. Resolution: 0.001mm/0.00005"	
	2199-1	Dual axis digital level and gyro angle meter	1. Range: single axis level: 4x90°, dual axis level: +40°, gyro angle meter: 360° 2. Resolution: single axis level 0.01°, dual axis level 0.01° gyro angle meter 0.1°	
	4120-10-DLC	Metric thread ring gauge	1. Nominal diameter: M10 2. Pitch: 1.5	
	4130-10-DLC	Metric thread plug gauge	1. Nominal diameter: M10 2. Pitch: 1.5	
5025-B1	2252-120+ 2508-10FWL	Comparison gauge	1. Range: 0-80mm/0-3.15" 2. Resolution: 0.001mm/0.00005"	
	2927-M200+ 2508-10FWL+ 2927-H+ 2927-S101+ 2927-S102+ 2927-S103+ 2927-S104+ 2927-J50+ 2927-D+ 2927-S201+ 2927-S201	Universal comparison gauge	1. Range: 0-200mm/0-8"(external diameter), 30-250mm/1.2-10"(internal diameter) 2. Resolution: 0.001mm/0.00005"	

Code	Includes	Description	Specification	Picture
5025-C1	9570-A5	Built-in wireless digital measuring tape	1. Range: 5m 2. Resolution: 0.001m	
	IST-42W20A	Built-in wireless digital torque wrench	1. Range: 4-20N.m 2. Resolution (Ra): 0.01N.m	
	ISR-C300WL	Built-in wireless Roughness tester	1. Range: X axis:17.5mm, Z axis: 320μm (-160μm~160μm) 2. Resolution (Ra): 0.001μm	
	9501-1200WL	Built-in wireless coating thickness gauge	1. Range: 0-1250μm 2. Resolution: 0.1μm (range<100μm), 1μm (range2100μm)	
	ISU-800DWL	Built-in wireless ultrasonic thickness gauge	1. Range: I-E 0.9-28mm/E-E 0.15-14mm 2. Resolution: 0.01mm/0.001mm	
	HDT-LP200WL	Built-in wireless Portable Ieab hardness tester	1. Range: HL170-960/HRC 17-70/HRB 13-109/HRA 7-89/ HB 20-655/HV 80-940/HSD 32-99.5/σb(rm) 255-2639N/mm ² 2. Resolution: 1HLD/1HV/1HB/0.1HRC/0.1HRB/0.1HRA/ 0.1HSD/1σb	
	ISV-K6015	Videoscope	1. Diameter: 6.0mm 2. Pixel: 0.92M	
5025-D	5325-VM100	Motorized zoom microscope	1. Magnification: 10-68.5X 2. Resolution: 1920x1080	